



STANDARD 3/8-INCH (10 MM) SHOWER VINYL COMBO

Part #: VPKG38H

The polycarbonate clear appearance wipe on the bottom of the door with a 45° drip rail creates a water-resistant seal and prevents water from escaping the shower. It can be easily snapped on the bottom of the door.

CLEAR BOTTOM WIPE WITH DRIP RAIL

- ♂ Glazing Thickness: 3/8 in (10 mm)
- 𝔆 Suggested Gap: 7/16 in (11 mm)
- 𝞯 Use on monolithic tempered glass

DUAL DUROMETER PVC SEAL AND WIPE

- 𝞯 Glazing Thickness: 3/8 in (10 mm)
- 𝔆 Suggested Gap: 1/4 in (6 mm)
- 𝞯 Use on monolithic tempered glass

H JAMB 180°

- ♂ For glass-to-glass application
- 𝞯 Glazing Thickness: 3/8 in (10 mm)
- 𝔆 Suggested Gap: 3/16 in (4.7 mm)

NOTES

- Ø Do not exceed either maximum weight or width when selecting the quantity.
- ${oldsymbol{arepsilon}}$ Project measurements from the edge of the glass.
- Always use dimensions to ensure accuracy.
- ${f \oslash}$ Do not use power tools or spray lubricant when installing.

Precision Glass Industries (PGI) reserves the right to update, revise and amend all technical data or content at any time. PGI shall have no liability of any kind or nature for any technical errors or omissions in this document. The information contained in this document is subject to change without notice. The PGI and AEON brands, trademarks, and logos are the property of Precision Glass Industries. All Rights Reserved. All contents copyright©2024. 03/18/24

Color: Clear

aeonhardware.com | info@aeonhardware.com